



ALPINE SANITATION & SUPPLIES LTD.

24 Ronson Drive, Unit 16, Etobicoke, Ontario M9W 1B4

Bus: (416)-744-2120 Fax: (416)-249-1859 Toll Free: 1-800 465-6198

*SW400 and SW600 glasswashers
provide high volume and top quality
performance in a compact, single unit.*

SW

Pass Through
Fully Automatic
Glasswashing Machine

New three pump injection system:

- Injector system allows the use of separate sanitizer and rinse aid resulting in real savings.
- Precisely calibrated pumps inject just the right amount of chemical each time – no guesswork – no waste.

Upper and lower wash and rinse arms produce sparkling clean glasses every time.

Cool final rinse water provides a fresh, cool glass ready for immediate use.

Available in either 4 foot or 6 foot models.

Two splash curtains.

Processes approximately 2000, 2-1/2" glasses/hr.

Available in either right-to-left or left-to-right operation.

Polypropylene conveyor virtually eliminates chipping of fine stemware.



SW400

Plan View

Front View

SW600

Plan View

Front View

Dimensions shown in inches and millimeters

NOTE: Both Doors: 21-1/2" [546] High
22" [559] Wide

Quick Facts

Capacity
2-1/2" glasses/hr. 2000

Water Consumption
Cold water (approx.) 2.8 US gpm;
10.6 liters/min;
2.24 imp. gpm
Hot water (initial fill) 3 US gallons;
11.35 liters;
2.4 imp. gallons
(Max use - approx. 10 US gph - 8.3 imp. gph)

Temperatures °F/C
Inlet water (hot) 140-160/60-71
Inlet water (cold) 75/24

Heating
Tank heat, electric (kw) 3

Conveyor
Speed inches/millimeters per min. 14/356

Utilities	
*Electrical: 208 - 230/60/1, 15 amp	
2	Hot water connection: 1/2" IPS Flow pressure 25-95 psi (173-656 kPa)
3	Cold water connection: 1/2" IPS Flow pressure 25-95 psi (173-656 kPa)
4	Drain connection: 1-1/2" tailpiece Connect to drain size according to local plumbing code.

***NOTE:** SW Models supplied with 4 ft. [1219] plug in cord.

Warning: Plumbing and electrical connections should be made by qualified personnel who will observe all the applicable plumbing, sanitary and safety codes.
Due to an ongoing value analysis program at Moyer Diebel, specifications in this catalog are subject to change without notice.

- ### Optional Accessories
- SW46C Waste Sink
 - SW47 Drain Tray and Waste Collector
 - SW12 S/S splash guards for SW400
 - SW24 S/S splash guards for SW600
 - SW48 S/S back panel for SW400
 - SW72 S/S back panel for SW600
 - Kit 264 Washdown hose
 - Kit 332 Casters; set of 4, 2 locking, 2 stationary

	Uncrated		Crated	
	SW400	SW600	SW400	SW600
Height*	38-1/2" [978]	38-1/2" [978]	49" [1244]	49" [1244]
Width	48" [1219]	72" [1882]	53" [1346]	76-1/2" [1942]
Depth	22" [559]	22" [559]	27-1/2" [698]	27-1/2" [698]
Ship Wt. lbs/kg	225/102	285/129	255/115	325/147

* Adjustable foot height - 1-1/4" [32]